

UTILITY HOSE

/// EPDM RUBBER

SPECIFICATION

This utility hose is constructed of rugged, lightweight EPDM rubber reinforced with synthetic cord. It has excellent heat, ozone, and weather resistance, with limited oil resistance. The design of this hose makes it a superior choice for agricultural spray and construction site applications where strength and versatility are a must. It is also ideal for general air and water applications.

MATERIALS

Utility hose is manufactured with lightweight EPDM rubber reinforced with synthetic cord.

APPLICATIONS

- Agricultural spray and construction site application where strength and versatility are a must
- General air and water applications

* The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.

RESISTANCE

Excellent heat, ozone and weather resistance, with limited oil resistance. (See list on website for listing of chemicals)

Operating temperature range: -40°F (-40°C) to 180°F (82°C)

Material: EPDM rubber

Color: Red

Hardness: Durometer 75+/-3

PACKAGING

Coils, reels

*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

PRESSURE RANGE

I.D. INCH	O.D. INCH	WALL INCH	WORKING PRESSURE (PSI @ 70°F)
1/2	3/4	1/8	200
5/8	1	3/16	200
3/4	1-1/8	3/16	200
1	1-3/8	3/16	200
1-1/4	1-3/4	1/4	200
1-1/2	2	1/4	200



WARNING: Not intended for use with potable water.



Create Item Number

900-13 A B R C D

e.g. **900-13206R00501:** Utility Hose 1/2" ID X 3/4" OD (1/8" Wall), Red, 50ft Reel

ID SIZE <u>A</u>	WALL <u>B</u>	LENGTH <u>C</u>	PACKAGE <u>D</u>
20 = 1/2"	6 = 1/8"	0050 = 50ft	1 = Coils
25 = 5/8"	8 = 3/16"	0075 = 75ft	5 = Reels
30 = 3/4"	9 = 1/4"	0100 = 100ft	
40 = 1"			
50 = 1-1/4"			
60 = 1-1/2"			

*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.



ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____

