

POOL & SPA VACUUM HOSE

/// LOW DENSITY POLYETHYLENE

SPECIFICATION

This pool and spa hose utilizes high grade, corrugated ultra-low density polyethylene. This design offers high melting temperatures, superior flexibility, and high puncture and tear resistance. The non-marking cover is abrasion resistant, crush-proof, and floats like a feather. It is top of the line for pool, spa, and vacuum applications. Screw-on pool cuffs are available for extensions and equipment connections.

ATTRIBUTES

- Design offers high melting temperature, superior flexibility, crush-proof, and buoyancy
- Color: Blue

MATERIALS

This pool and spa hose utilizes high grade, corrugated ultra-low density polyethylene.

APPLICATIONS

- Pool
- Spa
- Vacuum applications

RESISTANCE

Solvents, acids, alkalis and fuels.
(See list on website for listing of chemicals)

Max. vacuum, inches of mercury: 29"

Operating temperature range: -5°F (-21°C) to 150°F (66°C)

Material: Low density polyethylene

Color: Blue

Toxicity: Non-toxic

PACKAGING

Reels

*Custom lengths available in large quantity only. Contact your local rep to confirm availability.

PRESSURE RANGE

O.D. INCH	I.D. INCH	WALL INCH	WORKING PRESSURE (PSI @ 70°F)
1.58	1-1/4	.165	N/A
1.81	1-1/2	.155	N/A

 **WARNING: Not intended for use with potable water.**

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



Create Item Number

900-17 **A** **B** **C** **D**

e.g. 900-17500B00504: Pool & Spa Vac Hose 1-1/4" ID, Blue, 50ft Reel

ID SIZE A	WALL B	LENGTH C	PACKAGE D
50 = 1-1/4"	0 = Misc	0025 = 25ft	5 = Reels
60 = 1-1/2"		0050 = 50ft	



*Not all size, wall thickness and length combinations available. Contact your local rep to confirm availability.