SHOWER MODULE DRAIN

>> 827 / 828 SERIES

SPECIFICATION

Sioux Chief 827 or 828 series shower module drain shall be used where necessary in drainage systems. Shower drain shall have an outer locknut design with compression gasket connection for Sch. 40 ABS/PVC pipe. Snap-in strainer shall meet all applicable load and flow requirements for intended use.

Designed in accordance with ASME A112.18.2-2005 / CSA B125.2-05

MATERIALS

Strainer: Stainless steel (19 gauge) Drain body, locknut, compression nut:

827 Series: Brass

828 Series: Glass-filled polypropylene

Washers: Rubber, polyethylene Compression gasket: elastomer

STRAINER LOAD RATING

300 lbs. (light duty)

STRAINER FREE AREA

3.25 in²

FLOW RATE

6 GPM¹

DIMENSIONS

A: Connection size 2" Sch. 40 compression gasket

B: Strainer diameter 4-1/4" C: Overall height

1 Observed flow rate under test conditions at 0.375" head






827-2B



828-2



Choose Item Number

827-2B = Brass body model 828-2 = Polypro body model Snap-In Strainers - Available Separately: 827-2SPK1: Stainless steel strainer - snap-in 827-2RBPK2: Oil-rubbed bronze finish strainer - snap-in 827-2SNPK2: Satin nickel finish strainer - snap-in 827-2SMRPK1: Matte black finish strainer - snap-in 827-2SWPK1: White finish strainer - snap-in 827-2SPPK1: Polished brass finish strainer - snap-in

Note: All snap-in strainers are stainless steel base material with applied finish as indicated



03-25