ADJUSTABLE CLEANOUT FINISH FIXTURE

>> 834 SERIES

FinishLine[™]

SPECIFICATION

Sioux Chief 834 Series FinishLine finish fixture for adjustable cleanout system shall be used where necessary in drainage systems. Finish Fixture shall allow adjustment of 1.25" after the concrete pour when used with FinishLine rough-in fixtures. Scoriated cover shall meet all applicable load requirements for intended use.

Designed in accordance with ASME A112.6.3

MATERIALS

Ring/cover: Nickel-bronze, 304 Stainless steel, Ductile iron Head adapter: Ductile iron

COVER LOAD RATING

Nickel-Bronze / Stainless Steel: 4,000 lbs. (Medium duty)

Reinforced Nickel-Bronze / Stainless Steel: 15,000 lbs. (Special duty)

Ductile Iron: 6,000 lbs. (Heavy duty)

Reinforced Ductile Iron: 15,000 lbs. (Special duty)

DIMENSIONS

A: Top diameter - Round / Square 6-1/2" / 6-5/8"


B: Overall height 2-7/8" 4" C: Outlet diameter





834-4DHSR





Create Item Number

834-4DHAB

e.g. 834-4DHNRV: FinishLine cleanout finish fixture with round, vandal-resistant, nickel-bronze ring/cover

RING/COVER A	INSTALLED OPTIONS B
iR = Round ductile iron	V = Vandal-resistant cover screws
NR = Round nickel-bronze	S = Stamping (specify letters)
NQ = Square nickel-bronze	C = Carpet marker
SR = Round stainless steel	Z = Complies with BABAA ¹
SQ = Square stainless steel	H = Reinforced cover - Special Duty

Accessories - Available Separately: 832-S4: Leveling shim kit

832-EX4: Ductile iron extension adapter 832-W: Flexible locating bristle kit

Available for round nickel-bronze covers only



06-25