

ADJUSTABLE FLOOR DRAIN - ROUND TOP

862 SERIES

SPECIFICATION

Sioux Chief 862 Series coated cast iron adjustable floor drain with anchor flange, weep holes, clamping collar, adjustable round stainless steel top with vandal-resistant/heel-resistant, secured grate, 1/2" NPT trap primer (plugged) and bottom outlet. Designed in accordance with ASME A112.6.3

General purpose floor drain for use in kitchens, showers, restrooms and other finished areas with foot traffic.

MATERIALS

Drain body: cast iron

Clamping collar: cast iron

Head/strainer: 304 stainless steel


LOAD RATING

6,000 lbs.

DIMENSIONS

A: Connection size	2", 3", 4"	
B: Top diameter	5-3/8"	6"
C: Strainer adjustment	1.0" - 2.2"	1.0" - 2.5"
Strainer free-area	8.6 in ²	9.5 in ²

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



Create Item Number

862-ABCD

e.g. **862-236SRB:** Floor drain - 3" No-Hub connection, 6" round SS head/strainer with debris bucket

CONNECTION TYPE A

2 = No-Hub outlet
6 = Push-Joint outlet

CONNECTION SIZE B

2 = 2"
3 = 3"
4 = 4"

STRAINER DIAMETER C

5SR = 5-3/8" round
6SR = 6" round

OPTIONS D

B = Debris bucket
E = Drain head extension adapter¹
9 = Side-outlet connection²

1: Cast iron - MIP x FIP thread | 2: For 3" and 4" No-Hub connection only