ASTM F1960 PEX WATER HEATER CONNECTOR KIT

>> 694WG SERIES

HeatUp™

SPECIFICATION

Sioux Chief 694WG Series water heater connector kit shall be used where necessary in water distribution systems to connect PEX tubing to water heaters. ASTM F1960 PEX barb fitting ends are approved for use with ASTM F876 PEX tubing with PEX expansion rings. Please contact Sioux Chief representative for specific product information within the Sioux Chief ASTM F1960 product offering.

MATERIALS

Copper: Type-L copper tube

Valve Body (where applicable): No-Lead Brass* Swivel Nut: No-Lead brass* with EPDM gasket

WORKING LIMITS

80 PSI @ 200°F | 100 PSI @ 180°F | 160 PSI @ 73°F

INSTALLATION NOTES

Do NOT use pipe dope on FIP thread connections. Do NOT twist, kink, or loop flexible connectors. Always pressure test all joints before use.





694WG71022093



Item Number Series

694WGABC

e.g. 694WG71022093: Kit including 3/4" PEX x 3/4" FIP swivel hot-side connector, 3/4" PEX x 3/4" FIP swivel elbow cold-side connector, and 3/4" FIP swivel x 3/4" FIP swivel with 3/4" MIP branch connector for expansion tank

HOT-SIDE CONNECTOR A

49 = 3/4" PEX x 3/4" FIP swivel Flexible (18" long)

61 = 3/4" PEX x 3/4" FIP swivel elbow (3" x 4")

71 = 3/4" PEX x 3/4" FIP swivel (18" long)

COLD-SIDE CONNECTOR B

7520 = 3/4" PEX x 3/4" FIP swivel with ball valve (6" long)

7620 = 3/4" PEX x 3/4" FIP swivel with 3/4" FIP branch and ball valve (18" long)

4520 = 3/4" PEX x 3/4" FIP swivel Flexible with ball valve (18" long)

0220 = 3/4" PEX x 3/4" FIP swivel elbow with ball valve (3-1/8" x 7-1/2")

7720 = 3/4" PEX x 3/4" FIP swivel with ball valve (18" long)

1720 = 3/4" PEX x 3/4" FIP swivel with 3/8" OD compression TERV (18" long)

1820 = 3/4" PEX x 3/4" FIP swivel with 3/8" hose barb TERV (18" long)

1920 = 3/4" PEX x 3/4" FIP swivel with 1/2" F1960 PEX TERV(18" long)

EXPANSION TANK OPTION C

_ = No expansion tank (enter no option code)

91 = 3/4" FIP swivel x 3/4" FIP swivel with 3/4" MIP branch (15" long)

92 = 1" FIP swivel x 3/4" FIP swivel with 3/4" MIP branch (15" long)

93 = 3/4" FIP swivel x 3/4" FIP swivel with 3/4" MIP branch (11" long)

94 = 1" FIP swivel x 3/4" FIP swivel with 3/4" MIP branch (11" long)

Note: Not all option combinations are STOCK kits. For non-stock kits, a minimum of 25 pcs is required and extended lead times may apply.



^{*} Material is compliant with NSF-61 Annex G and California No Lead Plumbing Law